



# STRUCTURE

Blocking sunlight and heat, **TPO** Structure tarp **INNOGREEN® T**  
Low maintenance, self-cleaning, **PVC** Structure tarp **tentation®**

STO650

STO300

STO850

A-2BL



**tentation**  
**INNOGREEN®**

**tentation®** and **INNOGREEN® T** structure tarp is designed to combine functional and aesthetic aspects. Not only our product is durable and highly resistant to weather and UV, also known for its vibrant colors and various patterns. Wonpoong self-cleaning system ensures our structure tarp is the world's easiest to maintain.

## Features

- Strong durability and weatherability
- High-level resistance to UV and discoloration
- In widths up to 3.2 M
- Structurally stable and designed to minimize distortion

## Options

- Acrylic coating
- PDVF coating
- Anti-static treatment
- Anti-wicking treatment
- Anti-mildew treatment
- Fire retardant treatment
- UV resistant treatment



## STO650



| Total weight | Thickness    | Max. Width   | Tensile Strength       | Tear Strength      | Elongation | Adhesion             |
|--------------|--------------|--------------|------------------------|--------------------|------------|----------------------|
| gsm<br>(oz)  | mm<br>(mil)  | M<br>(inch)  | lbs/2.5cm<br>(N/5cm)   | lbs<br>(N)         | %          | lbs/2.5cm<br>(N/5cm) |
| 650<br>(19)  | 0.68<br>(27) | 2.50<br>(98) | 474/460<br>(4150/4028) | 76/85<br>(338/378) | 24/35      | 8/7<br>(70/60)       |

## STO300



| Total weight | Thickness    | Max. Width    | Tensile Strength       | Tear Strength      | Elongation | Adhesion             |
|--------------|--------------|---------------|------------------------|--------------------|------------|----------------------|
| gsm<br>(oz)  | mm<br>(mil)  | M<br>(inch)   | lbs/2.5cm<br>(N/5cm)   | lbs<br>(N)         | %          | lbs/2.5cm<br>(N/5cm) |
| 300<br>(9)   | 0.37<br>(15) | 3.70<br>(146) | 170/160<br>(1500/1400) | 35/30<br>(145/130) | 24/24      | 18/13<br>(158/110)   |

## STO850



| Total weight | Thickness   | Max. Width    | Tensile Strength       | Tear Strength        | Elongation | Adhesion             |
|--------------|-------------|---------------|------------------------|----------------------|------------|----------------------|
| gsm<br>(oz)  | mm<br>(mil) | M<br>(inch)   | lbs/2.5cm<br>(N/5cm)   | lbs<br>(N)           | %          | lbs/2.5cm<br>(N/5cm) |
| 850<br>(25)  | 1.6<br>(63) | 3.20<br>(126) | 418/416<br>(3660/3640) | 123/100<br>(545/440) | 21/26      | 23/21<br>(200/180)   |

## A-2BL



| Total weight | Thickness   | Max. Width   | Tensile Strength       | Tear Strength       | Elongation | Adhesion             |
|--------------|-------------|--------------|------------------------|---------------------|------------|----------------------|
| gsm<br>(oz)  | mm<br>(mil) | M<br>(inch)  | lbs/2.5cm<br>(N/5cm)   | lbs<br>(N)          | %          | lbs/2.5cm<br>(N/5cm) |
| 850<br>(25)  | 0.7<br>(28) | 2.50<br>(98) | 316/272<br>(2760/2380) | 100/83<br>(440/360) | 21/26      | 14/12<br>(120/105)   |



Digital Print Media

**anySign!**  
**anyFlex!**

---

Industrial Fabrics

**SuperTarp**

---

Tensile Structure Fabrics

**tentation**

---

Marine Fabrics

**AQUAFLOAT**

---

Geosynthetic Materials

**Geoloy®**

---

Eco-Freindly Materials

**INNOGREEN®**

---

Roofing Solutions

**SuperGuard™**